



Product certificate K58285-6

Issued 2025-04-01

Replaces K58285/05

Page 1 of 3

Glass fibre reinforced plastic (GRP) tanks, with or without catchment tanks, for above-ground storage of chemicals

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Certification, Kiwa declares that legitimate confidence exists that the products supplied by

Plasticon The Netherlands B.V.

as specified in this product certificate and marked with the Kiwa[®]-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with Kiwa evaluation guideline BRL K21011/03 "Glass fibre reinforced plastic (GRP) tanks, with or without catchment tanks, for above-ground storage of chemicals" d.d. 2024-09-01.

Ron Scheepers
Kiwa

Publication of this certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

CERTIFICATE

289171015

Kiwa Nederland B.V.
Sir Winston Churchillaan 273
Postbus 70
2280 AB RIJSWIJK
The Netherlands
Tel. +31 88 998 44 00
Fax +31 88 998 44 20
NL.Kiwa.info@Kiwa.com
www.kiwa.nl

Supplier
Plasticon The Netherlands B.V.
Havenkade 46
7553 GN HENGELO
The Netherlands
Tel. +31 541 858585
info@plasticoncomposites.nl
www.plasticoncomposites.com

Production location
Plasticon The Netherlands B.V.
Havenkade 46
7553 GN HENGELO
The Netherlands

Production location
Plasticon Poland SA
Marii Skłodowskiej-Curie 59
87-100 Toruń
Poland

Certification process
consists of initial and
regular assessment of:

- quality system
- product

Glass fibre reinforced plastic (GRP) tanks, with or without catchment tanks, for above-ground storage of chemicals

TECHNICAL SPECIFICATION

The tanks are designed for:

- Storage of chemicals in above ground installations;
- Atmospheric pressure i.e. with a design pressure ≤ 50 kPa;
- Inside or outside installation;
- With or without a thermoplastic liner;
- Maximum filling capacity = 95% of the nominal capacity;
- Fabricated in factory;
- Construction can be either:
 - Single or double walled, vertical cylindrical construction with a conical, flat or dished end roof or bottom, or
 - Single or double walled, horizontal cylindrical construction with dished ends;
- Without leak detection or pre-leakage detection;
- Subjected to a normal continuous operating temperature of fluid which can range between -40 °C and $+120$ °C.

The tanks are not suitable for:

- Combined installation such as a battery arrangement;
- Storage under pressure in excess of 50 kPa;
- Underground installation;
- Site built;
- Spherical tanks and tanks of irregular shape;
- Transport and distribution of fluids.

The catchment tanks are designed for the above ground secondary containment of the chemicals contained in the storage tanks. The catchment tanks have a volume of at least 100% of the nominal volume of the tank.

The tanks and catchment tanks are made from glass reinforced plastic (GRP). For the resistance to the stored chemicals the storage tanks are provided with a Single protective Layer (SPL) or a Chemical Resistant Layer (CRL) or a Thermoplastic Lining (TPL). The permitted TPL plastic materials are PVC-U, PP-H, PP-B, PP-R, PVDF, E-CTFE, FEP or PFA.

APPLICATION AND USE

The product certificate is only applicable if the requirements mentioned in paragraph 4.6 and 4.7 of the Evaluation Guideline are fulfilled. These are:

Installation and user instructions

The manufacturer shall provide proper written installation and users' instructions in the language of the country where the tank is to be installed and used. These instructions shall reference compliance with the national environmental regulations pertaining to the storage of chemicals. National regulations can stipulate requirements for preventing accidental impact to the tank and catchment tank and requirements for the overflow prevention and anti-siphon devices.

The following Evaluation Guidelines provide additional information pertaining to the installation of the tank and catchment tank in The Netherlands:

- BRL SIKB 7800 for tank installations;
- BRL-K910 for leak detection systems for the storage and/or transport of products in the liquid phase or gas phase.

In all cases the appendages used shall be resistant to the chemical stored and this shall be suitably demonstrated by the tank installer.

Documentation to be supplied with the tank and catchment tank

Every GRP-tank and catchment tank shall be supplied with at least the following documents:

- The documentation as required by NEN-EN 13121-3;
- Installation/user instructions in the language of the country where the tank is to be installed and used in.
The certification body shall approve these instructions;
- A unique tank/catchment tank compliance document with the approval of the certification body in relation to the product certificate.

Glass fibre reinforced plastic (GRP) tanks, with or without catchment tanks, for above-ground storage of chemicals

MARKING

The products are marked with the Kiwa mark.

Place of the mark

Each GRP tank and catchment tank shall be indelibly marked.

Compulsory indications

- Certification mark and certification number of the certification body;
- Manufacturer's name and/or manufacturer's trade mark;
- Serial number of the tank and/or catchment tank (serial number of storage tank and catchment tank must be different);
- Month and year of manufacture;
- Maximum filling capacity of the GRP tank and nominal capacity of the catchment tank in litres or m³;
- Name of the chemical to be stored in tank including the CAS number (Chemical Abstract Service number) along with the concentration;
- Location of the GRP tank: Inside or outside;
- Maximum design temperature of the chemical to be stored;
- Maximum design pressure of the tank.

The realization of the marks is as follows:

- Indelible;
- Clearly visible on the outside of the tank or catchment tank.

RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- Plastics The Netherlands B.V.
- and, if necessary,
- Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.